

Air-Pak® Fifty™

SCBA

- Cutting edge respiratory protection for first responders, municipal and industrial firefighters
- Time-tested record of reliable performance and rugged dependability
- Redundant safeguards promote an added margin of safety
- Tactile feel end of service indicator
- Includes Scott's workhorse regulator, the E-Z Flo®
- Available in 2216, 3000 and 4500 psi operating pressures
- Cylinder duration available in 30, 45 and 60 minutes
- TOP- \leftrightarrow -DOWN CONVERTIBILITY™ with AV-2000® facepiece
- AV-2000 allows for interface with Scott's full range of communication devices
- A lightweight, ergonomically designed harness system
- Places bulk of weight on hips instead of the shoulders
- Harness incorporates quick release take-up with parachute-style hardware
- Options include EBSS, Quick Connect E-Z Flo Regulator, Quick Charge, Airline pigtail, and integrated PASS



ORDERING INFORMATION ON BACK ➔

SPECIFICATION CARD

AIR - PAK FIFTY

Air-Pak® Fifty™

Part Number	Description of Product	Standard w/Case	Standard w/o Case	w/Quick Connect and case	w/Quick Connect w/o case	w/EBSS and Case	w/EBSS w/o Case	Weight* in lbs	Weight* in kgs
804484-XX	Air-Pak <i>Fifty</i> 2.2 with Aluminum Cylinder	-01	-02	-03	-04	-05	-06	30.5	13.8
804485-XX	Air-Pak <i>Fifty</i> 2.2 with Lightweight Cylinder	-01	-02	-03	-04	-05	-06	25.3	11.5
804486-XX	Air-Pak <i>Fifty</i> 2.2 with Featherweight Cylinder	-01	-02	-03	-04	-05	-06	22.0	10.0
804849-XX	Air-Pak <i>Fifty</i> 2.2 with Carbon Cylinder	-01	-02	-03	-04	-05	-06	18.9	8.6
804520-XX	Air-Pak <i>Fifty</i> 3.0 with Kevlar® Cylinder	-01	-02	-03	-04	-05	-06	25.0	11.3
805065-XX	Air-Pak <i>Fifty</i> 3.0 with Carbon Cylinder	-07	-02	-08	-01	-09	-10	22.3	10.1
804490-XX	Air-Pak <i>Fifty</i> 4.5 with 30 Min. Kevlar Cylinder	-01	-02	-03	-04	-05	-06	20.3	9.2
804846-XX	Air-Pak <i>Fifty</i> 4.5 with 30 Min. Carbon Cylinder	-01	-02	-03	-04	-05	-06	18.9	8.6
804491-XX	Air-Pak <i>Fifty</i> 4.5 with 45 Min. Kevlar Cylinder	-01	-02	-03	-04	-05	-06	26.2	11.9
804847-XX	Air-Pak <i>Fifty</i> 4.5 with 45 Min. Carbon Cylinder	-01	-02	-03	-04	-05	-06	23.1	10.5
804492-XX	Air-Pak <i>Fifty</i> 4.5 with 60 Min. Kevlar Cylinder	-01	-02	-03	-04	-05	-06	29.4	13.3
804848-XX	Air-Pak <i>Fifty</i> 4.5 with 60 Min. Carbon Cylinder	-01	-02	-03	-04	-05	-06	26.1	11.8
804936-XX	Air-Pak <i>Fifty</i> 2.2 less Cylinder	-01	-02	-03	-04	-05	-06	9.5	4.3
805065-XX	Air-Pak <i>Fifty</i> 3.0 less Cylinder	-11	-03	-12	-04	-13	-06	9.5	4.3
804935-XX	Air-Pak <i>Fifty</i> 4.5 less Cylinder	-01	-02	-03	-04	-05	-06	9.5	4.3

* Normal weights in lb/kg (with charged cylinders) do not include options.



APPROVALS

- ETL listed for Intrinsic Safety Class I, II, III, Div. I, Groups A, B, C, D, E, F and G per ANSI/UL 913
- NFPA - 1981 (1997 Edition) compliant
- NIOSH approved
- TC13F-80 30 min 2216 psig, TC13F-76 30 min 4500 psig, TC13F-212 45 min 4500 psig, TC13F-96 60 min 4500 psig



NBC Safety
World Leaders in Defense Technology

fax: (858) 488-6320 tel: (858)488-3300

sales@NBCsafety.com

www.NBCsafety.com

H/S 6239 A 1/01

SPECIFICATION CARD